

IN THE CLAIMS:

Please cancel claims 5 and 13 without prejudice or disclaimer.

Please amend claim 6 and 14 as follows:

1-5. (Cancelled)

6. (Currently Amended) A plasma resistant seal comprising:

a plasma seal made entirely of a material provided with a plasma resisting performance, the plasma seal being provided in a plasma irradiating side of a packing made of a plasma resistant FKM rubber containing no mineral component and serving as a main seal, said plasma seal being made entirely of a non-filler type of polytetrafluoroethylene and said packing being an O-ring,

a diameter of said packing in a height direction of said packing being larger than a ~~width~~ height of said plasma seal as measured in the height direction of said packing,

the packing being attached to a packing installation groove provided in an installation member, and the plasma seal being attached to a plasma irradiation side of the installation groove, the packing installation groove being formed in an approximately quadrangular cross section shape, a side wall portion of the packing installation groove being formed at a right angle with respect to an end surface of the

installation member in the plasma irradiating side, and the plasma seal being compressed between the side wall portion of the packing installation groove and the packing when irradiating a plasma to said plasma resistant seal, the height direction of the packing being in a direction along the side wall portion;

the plasma seal having an arch cross sectional shape with a concave surface engaging the packing and having a convex surface engaging the side wall portion of the packing installation groove, and

the convex and concave surfaces of the plasma seal being arranged along a direction generally orthogonal to a plasma irradiation direction so that the packing is prevented from protruding into a gap extending from the plasma irradiation direction.

7-13. (Cancelled)

14. (Currently Amended) An apparatus for manufacturing a semiconductor device by irradiating plasma with using a plasma resistant seal, said plasma resistant seal comprising:

a plasma seal made entirely of a material provided with a plasma resisting performance, the plasma seal being provided in a plasma irradiating side of a packing made of a plasma resistant FKM rubber containing no mineral component and serving

as a main seal, said plasma seal being made entirely of a non-filler type of polytetrafluoroethylene and said packing being an O-ring,

a diameter of said packing in a height direction of said packing being larger than a ~~width~~ height of said plasma seal as measured in the height direction of said packing,

the packing being attached to a packing installation groove provided in an installation member, and the plasma seal being attached to a plasma irradiation side of a same installation groove, the packing installation groove being formed in an approximately quadrangular cross section shape, a side wall portion of the packing installation groove being formed at a right angle with respect to an end surface of the installation member in the plasma irradiating side, and the plasma seal being compressed between the side wall of the packing installation groove and the packing when irradiating a plasma to said plasma resistant seal, the height direction of the packing being in a direction along the side wall portion,

the plasma seal having an arch cross sectional shape with a concave surface engaging the packing and a convex surface engaging the side wall at the plasma irradiation side of the packing installation groove, and

the convex and concave surfaces of the plasma seal being arranged along a direction generally orthogonal to a plasma irradiation direction so that the packing is prevented from protruding into a gap extending from the plasma irradiation direction.

15-18. (Cancelled)